

Fugro Development Centre 5 Lok Yi Street, Tai Lam Tuen Mun, NT Hong Kong

Client Ref.

: --

Report No. 202519PC200090

Page 1 of 5

# REPORT ON TESTING OF FLOAT OPERATED GUNMETAL VALVE

**Information Supplied by Client** 

Client Wah Hung Fire Prevention Equipment Co., Limited

Client Address G/F, No.129, Tai Nan Street, Prince Edward, Kowloon, Hong Kong

Project Testing of Float Operated Gunmetal Valve

Sample Description Float Operated Gunmetal Valve

Brand : WAH HUNG Model : WH024-40

Boby Marking : M DN 40

Country of Origin : China

Manufacturer : Wah Nan Fire Fighting Equipment Co., Ltd.

**Laboratory Information** 

Lab. Sample I.D. : PC200090/1

Date Received : 07 May 2020 & 05 June 2020

Date Test Started : 17 June 2020
Date Test Completed : 16 July 2020

Test Method BS 1212 : part 1 : 1990, BS EN 12164 : 2016 and

BS EN 1982: 2008

### **Test Results**

#### 1. Dimensions

BS 1212 : part 1 : 1990 (Section 3) and Base on Manufacturer Requirement

Lab. Sample I.D.	Nominal Size (DN)	BS Requirement (Nominal Size) (DN)	H1 (mm)	H2 (mm)	l	acturer rement	Results
PC200090/1	40mm	40mm (1-1/2")	70	90	H1 (mm)	H2 (mm)	Pass
	(1-1/2")				70	90	



Fugro Development Centre 5 Lok Yi Street, Tai Lam Tuen Mun, NT Hong Kong

Page 2 of 5

Client Ref. :

: --

Report No. : 202519PC200090

### 2. HYDRAULIC PRESSURE TEST

(BS 1212 : Part 1 : 1990,cluase 24)

Lab Sample I.D.	Hydraulic pressure test				
PC200090/1	Test Pressure (bar)	Duration (min.)	Observation	Remark	
	20	15	No leakage was detected during the test	Pass	
BS Requirement	20	15 <sup>+1</sup> <sub>- 0</sub>	No leakage or sweating	do ma	

### 3. SHUT-OFF TEST

(BS 1212 : Part 1 : 1990,cluase 24)

(BC 1212.1 att 1. 1990,cluase 24)						
Lab Sample I.D.	Shut-off test					
		Test Pressure (bar)	Duration (sec.)	Observation	Remark	
PC200090/1	1st test	3	60	No leakage was detected during the test	Pass	
	2 nd test	7				
	3 rd test	14				
BS Requirement	for low pressure valve	3		No leakage		
	for medium pressure valve	7				
	for high pressure valve	14				



Fugro Development Centre 5 Lok Yi Street, Tai Lam Tuen Mun, NT Hong Kong Page 3 of 5

Client Ref.

: --

Report No. : 202519PC200090

# 4. Chemical Composition (Body)

Testing items	Results	Specification according to BS EN 1982 : 2008 Grade CC491K castings
1. Copper (Cu) content, %	85.9	83.0 – 87.0 <sup>1)</sup>
2. Nickel (Ni) content, %	0.41	2.0 max.
3. Phosphorus (P) content, %	<0.03	0.10 max.
4. Lead (Pb) content, %	5.1	4.0 – 6.0
5. Tin (Sn) content, %	4.6	4.0 - 6.0
6. Zinc (Zn) content, %	4.2	4.0 - 6.0
7. Aluminium (Al) content, %	<0.01	0.01 max.
8. Iron (Fe) content, %	0.06	0.3 max.
9. Sulfur (S) content, %	<0.04	0.10 max.
10. Antimony (Sb) content, %	0.05	0.25 max.
11. Silicon (Si) content, %	<0.01	0.01 max.

Remark: 1) Including nickel

Note: Based on the test results of the submitted sample, it is found that the sample complies with the chemical composition specification of BS EN 1982 : 2008 Grade CC491K castings. The chemical composition results are obtained from our test report no. 20259EN201532

### 5. Chemical Composition (Piston)

Testing items	Results	Specification according to BS EN 12164 : 2016 Grade CW617N
1. Aluminum (Al) content, %	<0.01	0.05 max.
2. Copper (Cu) content, %	58.1	57.0 – 59.0
3. Nickel (Ni) content, %	<0.08	0.3 max.
4. Lead (Pb) content, %	1.8	1.6 – 2.5
5. Tin (Sn) content, %	0.13	0.3 max.
6. Zinc (Zn) content, %	39.6	Remainder
7. Iron (Fe) content, %	0.16	0.3 max.
Hence, others content, %	<0.2	0.2 max.

Note: Based on the test results of the submitted sample, it is found that the sample complies with the chemical composition specification of BS EN 12164 : 2016 Grade CW617N.

The chemical composition results are obtained from our test report no. 202519EN201714.



Fugro Development Centre 5 Lok Yi Street, Tai Lam Tuen Mun, NT Hong Kong Page 4 of 5

Client Ref.

Report No. 202519PC200090

### 6. Chemical Composition (Lever)

Testing items	Results	Specification according to BS EN 1982 : 2008 Grade CC491K castings	
1. Copper (Cu) content, %	86.7	83.0 – 87.0 <sup>1)</sup>	
2. Nickel (Ni) content, %	0.44	2.0 max.	
3. Phosphorus (P) content, %	<0.03	0.10 max.	
4. Lead (Pb) content, %	4.4	4.0 - 6.0	
5. Tin (Sn) content, %	4.2	4.0 - 6.0	
6. Zinc (Zn) content, %	4.5	4.0 - 6.0	
7. Aluminium (Al) content, %	<0.01	0.01 max.	
8. Iron (Fe) content, %	0.17	0.3 max.	
9. Sulfur (S) content, %	<0.04	0.10 max.	
10. Antimony (Sb) content, %	0.04	0.25 max.	
11. Silicon (Si) content, %	<0.01	0.01 max.	

Remark: 1) Including nickel

Note: Based on the test results of the submitted sample, it is found that the sample complies with the chemical composition specification of BS EN 1982 : 2008 Grade CC491K castings.

The chemical composition results are obtained from our test report no. 20259EN201532

# 7. Summary of Results (apply only to sample tested)

**Dimensions** -- Pass Hydraulic Pressure Test -- Pass Shut-off Test -- Pass Chemical composition (Body) -- Pass Chemical composition (Piston) -- Pass Chemical composition (Lever) -- Pass

Remark: 1.) The test results relate only to the samples tested.

- 2.) No electroplating materials were observed on the internal water passage surfaces of the sample under a non-destructive and unaided visual inspection.
- 3.) The test sample is shown in the photograph on page 5 of this report.

Ng Shu Shing Chris

Assistant Manager (Plumping Components)



Fugro Development Centre 5 Lok Yi Street, Tai Lam Tuen Mun, NT Hong Kong

Page 5 of

Client Ref. : --

Report No. : 202519PC200090



**Test Sample** 



**Test Sample** 



**Body Marking** 

\*\* End of Report \*\*